

# Technical Information

## UPster PF 600

**Execution for: Australia**

Country of production: China

**Utensil washing machine**

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft warm water 0-3°dH



Sample illustration

### Technical data

<b>Rack capacity/h (theoretical)</b>	30 / 15 / 10 racks/h
<b>Programme cycle *</b>	120 / 240 / 360 s
<b>Rack dimension</b>	670 x 630 mm
<b>Entry height</b>	600 mm
<b>Dimensions (W x Hmin x D)</b>	870 x 1600 x 760 mm
<b>Electrical feeding cable</b>	3-phase current 3N PE 400V 50Hz* Total connected load: 11.2 kW max. rated current: 18.5 A
<b>Local fuse protection</b>	20 A
<b>Protection class of the machine</b>	IP X4
<b>Equipment</b>	MIKE control Infrared interface for wireless communication Drain pump Boiler safety device Automatic self-cleaning when tank is drained
<b>Fresh water line</b>	Air gap 'AA' in accordance with EN 1717 with booster pump
<b>Fresh water supply</b>	Minimum flow pressure 60 kPa / 0.6 bar in front of solenoid valve Maximum pressure 500 kPa / 5.0 bar Max. supply water temperature 60 °C
<b>Flow rate</b>	4 l/min
<b>Final rinse water quantity</b>	4 liters/cycle
<b>Boiler</b>	Contents: 10.5 l Heater: 9.00 kW Temperature: 83 °C Tank / boiler interlocked
<b>Wash tank</b>	Filling: 60 l Heater: 6.00 kW Temperature: 60 °C

# Technical Information

<b>Wash pump</b>	Performance: 2.00 kW
<b>Dosing of rinse aid</b>	Hose pump (24 V) with time control and suction lance
<b>Detergent dosage</b>	Hose pump (24 V) with time control and suction lance
<b>Material</b>	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4404
<b>Heat emission</b>	for 15 programme cycles/h total: 2.8 kW perceptible: 1.9 kW latent: 0.9 kW
<b>Ventilation flow rate</b>	710 m <sup>3</sup> /h
<b>Steam emission</b>	1.3 kg/h
<b>Sound level</b>	68 dB(A)
<b>Net / gross weight</b>	165.0 kg / 190.0 kg (standard packaging)
<b>Packaging dimensions (W x H x D)</b>	1050 x 1750 x 1000 mm (standard packaging)

## \*Note:

Electrical equipment suitable for supply voltage:  
3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)  
1N PE 230 V 50 HZ (1N PE 220-240 V 50 Hz)